

PRESS RELEASE

NEW DENSITOMETER

DDS3

NDT Equipment Supplies Limited in Wellingborough are pleased to launch the new hand held portable **Densitometer DDS3**. This unit replaces the old and trusted DDS2 which has now been discontinued.



FEATURES

- Ease of use
- Single handed operation
- Integrated probe eliminates cables
- Small enough to fit in a pocket
- Long battery life
- Rugged construction
- Uses a universally obtainable PP3 9V battery
- Battery can be replaced without needing tools
- Low battery icon displayed on the LCD

OPERATION

Switch the DDS3 on using the switch which is positioned next to the probe, place the probe on the viewer and using the thumbwheel set for 0.00 on the LCD display. Place your film on the viewer and place the DDS3 probe directly on to the film where the reading is required and the LCD will now display the density of the film.

SPECIFICATION

Range: 2,000 to 50,000 Lux.

Density: 0.00 to 4.20

Accuracy: +/- 0.05

Probe: Temperature compensated

Display: 3.5 digit LCD with 12.5mm character height

Battery: Type PP3 9 Volt

Size: 118.5 x 58.5 x 33.5 (Including probe)

Weight: 150 gm (including battery)

Operating temperature range: -10° to 65° C

NDT Equipment Supplies Ltd
11 Vaux Road, Finedon Road Industrial Estate
Wellingborough, Northants. NN8 4TG
Tel: 01933 274833 Fax: 01933 274113
saleshire@ndt-es.co.uk www.ndtes.co.uk